


Model NO: HD Wireless PTZ Dome IP Camera FI9928P	Features:
	HD Wireless PTZ Dome IP Camera.
	◆ 2.0 Megapixel HD Pan/Tilt/Zoom Wireless Dome IP Camera
	◆ 4x zoom lens provide detailed view
	◆ H.264 video Compression
	◆ Day/Night Surveillance, IR LEDs On/Off Auto Switch
	◆ With 6pcs IR-Array lights, Night Vision Range up to 60m
	◆ Motion Detection alarm via E-Mail and FTP
	◆ Supports Auto Focus
	◆ Compatible with free Foscam iOS and Android APP
	◆ Free Foscam DDNS Service Embedded
	◆ Supports PnP connection
	◆ Supports IEEE 802.11n Wireless Connection
	◆ Supports WEP, WPA and WPA2 Encryption
◆ Supports two-way Audio	
◆ Supports I / O interfaces	

Specification		
ITEMS	FI9928P	
Image Sensor	Sensor	Sony High Definition Color CMOS Sensor
	Display Resolution	2.0 Megapixel
	Min. Illumination	0 Lux (With IR Illuminator)
Lens	Lens Type	Glass Lens
	focal length	f:2.8~12mm
	Aperture	F1.6
	Angle of View	Horizontal:40°~105° Diagonal :48°~125°
Video	Image Compression	H.264
	Image Frame Rate	25fps maxmium, downward adjustable
	Resolution	1080P(1920x1080),720P(1280 x 720), VGA(640 x 480), QVGA(320 x 240)
	Stream	dual stream
	Image adjustment	The hue, brightness, contrast, saturation, sharpness are adjustable
	Flip image	flip and mirror
	Infrared mode	Automatic or manual
	Pan/Tilt Angle	Horizontal:355° & Vertical: 90°
Audio	Input/Output	External 3.5mm standard interface for two-way audio
	Audio Compression	PCM
Network	Ethernet	One 10/100Mbps RJ45 port
	Wireless Standard	IEEE802.11b/g/n
	Data Rate	IEEE802.11b: 11Mbps(Max.); IEEE802.11g: 54Mbps(Max.); IEEE802.11n: 150Mbps(Max.).
	Wireless Security	WEP, WPA, WPA2
	Network Protocol	IP、TCP、UDP、HTTP、HTTPS、SMTP、FTP、DHCP、DDNS、UPnP、RTSP
System Requirements	Operating System	Microsoft Windows XP, Vista, 7, 8; Mac OS iOS、Android
	Browser	Microsoft IE Mozilla Firefox; Google Chrome; Apple Safari.
Other Features	Motion Detection	Alarm via E-Mail, upload alarm snapshot to FTP
	Privacy Zone	Set privacy zone manually
	User Accounts	Three levels user role
	Firewall	Supports IP Filtering
	Reset	Reset button is available
Power	Power Supply	DC 12V/2.0A
Physical	Power Consumption	10Watts (Max.)
	Dimension(LxWxH)	234*209*138 mm
	Net Weight	1850g
Environment	Operating Temperature	-20°C ~ 60° (-4°F ~ 140°F)
	Operating Humidity	20% ~ 85% non-condensing
	Storage Temperature	-20°C ~ 60° (-4°F ~ 140°F)
	Storage Humidity	0% ~ 90% non-condensing
Certification	CE, FCC, RoHS	