



SPECIFICATION

Model	HT1612	
Power	Power Adapter Voltage□	Input 100-240V/AC 50/60Hz
	The maximum power supply machine	240W
Protection level	Mould	+ -4KV
	Differential mode	+ -1KV
Network Connector □	Network Port□	1~16 port: :10/100Mbps PoE Ethernet port WAN1/WAN2 port:10/100/1000Mbps
	Transmission Distance	Extend switch is default OFF, state(1~16 port): 100m Extend switch is ON, state:(1~16 port): 250m WAN1/WAN2 port: 100m
	Transmission Medium	Cat5/5e/6 standard network cable
Network Switch □	Network Standard	IEEE802.3/10BASE-T
		IEEE802.3u/100BASE-TX
		IEEE802.3x Flow Control, IEEE802.3az
	Maximum Frame Size	1536 Bytes□
	MAC address list	2K
	Backplane bandwidth	1Gbps
	PoE Standard	IEEE802.3af/at
Power Over Ethernet □	PoE Power Supply Type□	End-Span(4/5+;7/8-)
	PoE Power Consumption	af,at Adaptive (every port)
LED Status Indicator	POE Ethernet	When the PoE is powered, 1-16 LEDs are green
		When accessing Ethernet, ports 1-16 are yellow
Environmental	Working temperature	0℃ ~55℃
	Working humidity	10%-90% non-condensing
	Storage temperature	-40℃ ~70℃
	Storage Humidity	5%-95% RH non-condensing
Mechanical	Dimension (L x W x H) mm□	290*200*44
	Weight	3.5KG
	Material	SECC
	Color	Dark gray
Stability	MTBF	>30000h