



SPECIFICATION

Model	PT5A033HTC200NS
Camera	
Image Sensor	1/2.8" SONY 2.4MP CMOS Sensor
Horizontal Resolution	2MP
S/N Ratio	>50db
PTZ	
Horizontal Rotation Speed	45°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	30°/s
Tilt Rotation Range	0°~90°
Auto Flip	Support
Ratio Speed	Support
360° Scan	Support
A-B Scan	Support
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
Lens	
Focus Length	4.6mm-152mm
Focus Control	33X Optical Zoom
Night Vision	
Infrared LED	Φ 42x6PCS
IR Range	60m
Auto Control IR LED	PWM
Communication	
Communication Protocol	UTC
Communication interface	COAXIAL CABLE
Interface	
Audio	/
Alarm	/
General	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Heater & Blower	Auto temperature control
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	29.5x28x17(cm)
Weight	4.2Kgs