



## SPECIFICATION

<b>Model</b>	<b>PT5E122S500</b>
<b>Camera</b>	
Image Sensor	1/2.5" Aptina 5.1MP High Performance CMOS Sensor
Image Resolution	5MP
Compression	H.264/H.265
S/N Ratio	>50db
<b>PTZ</b>	
Horizontal Rotation Speed	120°/S
Horizontal Rotation Range	0°~360°
Tilt Rotation Speed	60°/s
Tilt Rotation Range	0°~93°
Preset Points	220
Guard Tours	3 groups
Guard Points	Max.16 points
<b>Lens</b>	
Focus Length	3.9mm-85.5mm
Focus Control	22X Optical Zoom
<b>Night Vision</b>	
Infrared LED	7PCS Array IR LEDs + 2PCS Laser Lamp
IR Range	180m
Day-night mode	AUTO
<b>Network</b>	
Network protocol	TCP/IP, HTTP, FTP, RTSP, UPnP, DNS, NTP, RTP, UDP, IGMP,P2P
ONVIF	Support
Network interface	Built-in RJ45 network interface,support 10M/100M IP DATA
Stream type	Main Stream / Sub Stream / MJPEG
<b>Interface</b>	
Audio	Optional
Alarm	/
POE	/
<b>General</b>	
Weatherproof	IP66
Operating Temperature	Indoor: 0°~ +40° Outdoor: -40°~ +60°
Operating Humidity	≤90% Non Condensing
Power	DC12V 2A/3A
Lightning Protection	Transient voltage 6000V
Dimension	25x21.5x41(cm)
Weight	4.9Kgs