



SPECIFICATION	
Model	XVR2104D
System	
Main Processor	HI3521A
Operating System	Embedded LINUX
Video	
Input	Analog: 4*(TVI/AHD: 5M; AHD/TVI/CVI: 4M; AHD/TVI: 3M; AHD/TVI/CVI: 1080P/720P; Analog: 960H) Analog+Network:2*Analog+7*network(Max 8MP) Network: 16*network(Max 8MP)(Total incoming bandwidth ≤80M)
Input	4CH BNC
Signal Type	Analog/AHD/CVI/TVI 2.0/TVI 3.0/Network
Output	1 HD,1 VGA, 1CVBS
Audio	
Input	4Channel, RCA
Two-way Audio	NO
Output	1 Channel, RCA
Alarm	
Sensor Input	NO
Output	NO
Motion Detection	4 Channel(max 16 Channel in pure network mode)
Trigger Events	Recording, Alarm, Email, Screen tips, Buzzer
Email Alarm	Send Image to The Designated E-mail
PTZ	
Interface	RS485
Protocol	Pelco-D, Pelco-P
Baud Rate	110~921600
Address	0~255
Display	
VGA	resolution: 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
HD Output	Resolution:2560*1440/30Hz, 1920 × 1080P /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz,1024 × 768 /60Hz
Display Split	16 Channel/9 Channel/8 Channel/4 Channel / 1Channel
Privacy Masking	1 Rectangular Zones (Each camera)
OSD	Camera title, Time, Video loss, Alarm, Motion detection, Recording
Recording	
Video Compression	H.264
Audio Compression	G711u
Resolution	5MP(2592×1944),5MP_HALF(1296×1944),4MP(2560×1440),4MP_HALF(1280×1440),3MP(2048×1536),1080P(1920×1080),720P(1280×720),960H(P:960×576/N:960×480)
Video Quality	worst/worse/ordinary/well/best
Record Rate	Analog: PAL:5MP(2592×1944 4*12fps),5MP_HALF(1296×1944 4*20fps), 4MP(2560×1440 4*15fps),4MP_HALF(1280×1440 4*25fps),3MP(2048×1536 4*18fps);1080P(1920×1080 4*25fps),720P(1280×720 4*25fps), 960H(960×576 4*25fps) NTSC: PAL:5MP(2592×1944 4*12fps),5MP_HALF(1296×1944 4*20fps), 4MP(2560×1440 4*15fps),4MP_HALF(1280×1440 4*30fps),3MP(2048×1536 4*18fps),1080P(1920×1080 4*30fps),720P(1280×720 4*30fps), 960H(960×480 4*30fps) Pure IP: PAL:4k@6×25fps,5MP@8×25fps,4MP@11×25fps,3MP@11×25fps,1080P@16×25fps,960P@16×25fps,720P@16×25fps,D1@16×25fps NTSC: 4k@6×30fps,5MP@8×30fps,4MP@11×30fps,3MP@11×30fps,1080P@16×30fps, 960P@16×30fps, 720P@16×30fps, D1@16×30fps
Record Mode	Manual\Timer\Motion Detection
Playback & Backup	
Decode Capability	4CH 1080P@30fps
Sync Playback	Pure Analog: 4CH 5M@12fps, 4CH 4M@15fps, 4CH 3M@18fps, 4CH 1080p@30fps Mix Mode: 2CH 1080P@30fps+1CH 1080N@12fps Pure IPC: 1CH 4K@30fps, 1CH 5MP@30fps, 2CH 4MP@30fps, 3CH 3M@30fps, 4CH 1080P@30fps, 4CH 960P@30fps, 4CH 720P@30fps
Remote Playback	4 Channel / 1 Channel
Search Mode	ALL, Channel, Manual, Time, Date, Motion Detection
Playback Functions	Play, Pause, Stop, Fast play, Rewind
Smart Phone Playback	4 Channel
Backup Mode	USB Device/Network
Network	
Interface	1 RJ45 10M/100 Adaptive Ethernet Interface
Network Functions	HTTP, IPv4,IPv6, TCP/IP, SMTP, DHCP, DNS, PPPOE, DDNS, NTP, FTP, UPNP
DDNS	Dyndns, changeip, no-ip, Oray, A-PRESS, MYQSEE, SKDDNS, SMART-EYES
Web Browser	IE8-11, Google Chrome (IE Tab), Firefox (IE Tab)
CMS Software	Support Windows 7/ Windows 8/Windows 10
Extra Stream	CIF(1~25fps)
Smart Phone	iPhone, ipad, Android, Android pad
Hard Disk Driver	
Interface Type	1 SATA Interface
Capacity	2.5"/3.5" SATA, Up to 6TB
General	
Language	Chinese, English, Polish, Czech, Russian, Thai, Hebrew, Arabic, Bulgarian, Farisa German, French, Portuguese, Turkic, Spanish, Italian, Hungarian, Romanian, korean, Dutch, Greek
UTC Control	YES
USB Interface	2 USB 2.0 Interfaces
Power consumption	DC 12V ≤6W (Without Hard Disk)
Working Environment	-10~55°C/10~90%
Dimension (W×D×H)	260*215*43(mm)
Weight	2.0kg (Without HDD)